


XGQT32

Flexible Coupling



100TONG Model XGQT32 is Ductile Iron Grooved Flexible Couplings. XGQT32 is designed for use on Schedule 5, schedule 10, schedule 40, GB/T3091, JIS G3452, WGalweld 5 and WGalweld 7 pipe. Sizes of XGQT32 from 25mm–300mm/1" – 12". Pressure of XGQT32 conform to the list from UL and FM.

Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Bolt Size No.–Size mm	Dimensions mm/in			UL	FM
				Ø	L	H		
25 1	33.7 1.327	500 3.45	2–M10 × 45	58 2.283	100 3.937	44 1.732	●	●
32 1¼	42.4 1.669	500 3.45	2–M10 × 45	67 2.638	107 4.213	44 1.732	●	●
40 1½	48.3 1.900	500 3.45	2–M10 × 45	72 2.835	111 4.370	44 1.732	●	●
50 2	60.3 2.375	500 3.45	2–M10 × 55	85 3.346	124 4.882	44 1.732	●	●
65 2½	73.0 2.875	500 3.45	2–M10 × 55	99 3.898	138 5.433	45 1.772	●	●
65 2½	76.1 3.000	500 3.45	2–M10 × 55	102 4.016	142 5.591	45 1.772	●	●
80 3	88.9 3.500	500 3.45	2–M12 × 60	116 4.567	165 6.496	45 1.772	●	●
100 4	108.0 4.250	500 3.45	2–M12 × 65	138 5.433	187 7.362	48 1.890	●	●
100 4	114.3 4.500	500 3.45	2–M12 × 65	141 5.551	190 7.480	49 1.929	●	●
125 5	133.0 5.250	300 2.07	2–M12 × 75	164 6.457	213 8.386	48 1.890	●	●
125 5	139.7 5.500	300 2.07	2–M12 × 75	167 6.575	218 8.583	49 1.929	●	●
125 5	141.3 5.563	300 2.07	2–M12 × 75	167 6.575	219 8.622	49 1.929	●	●
150 6	159.0 6.250	300 2.07	2–M12 × 75	190 7.480	240 9.449	49 1.929	●	●
150 6	165.1 6.500	300 2.07	2–M12 × 75	192 7.559	245 9.646	50 1.969	●	●
150 6	168.3 6.625	300 2.07	2–M12 × 75	200 7.874	250 9.843	49 1.929	●	●
200 8	216.3 8.504	300 2.07	2–M16 × 85	250 9.843	316 12.441	59 2.323	●	●
200 8	219.1 8.625	300 2.07	2–M16 × 85	253 9.961	319 12.559	59 2.323	●	●
250 10	267.4 10.512	300 2.07	2–M22 × 130	307 12.087	388 15.276	65 2.559	●	●
250 10	273.0 10.748	300 2.07	2–M22 × 130	317 12.48	401 15.787	63 2.48	●	●
300 12	318.5 12.520	300 2.07	2–M22 × 130	360 14.173	450 17.717	65 2.559	●	●
300 12	323.9 12.752	300 2.07	2–M22 × 130	375 14.764	455 17.913	64 2.52	●	●